

Modelli - Models - Modèles - Modelle			SIRIO-M	SIRIO-T	
Corse Travels Courses Verfahrwege	- Longitudinale - Longitudinal - Längs - Longitudinale		mm (in)	4.000 - 12.000 > (157,5 - 472,5 >)	----
	- Verticale - Vertical - Vertikal - Verticale			2.000 - (78,7)	
	- Trasversale Ram - Ram cross travel - Ram Querweg - Transversale béliier		1.200 - (47,25)		
	- Trasversale montante - Column cross travel - Ständer Querweg - Transversale montant		----		1.000 - 1.500 - 2.000 (39,4 - 59 - 78,7)
Avanzamenti Feeds Vorschübe Avances	- Velocità di avanzamento - Feed rate - Vorschubgeschwindigkeit - Vitesse d'avance		X,Y,Z	mm/1' (ipm)	20.000 (788)
	- Spinta di lavoro asse - Feed rate - Vorschubgeschwindigkeit - Vitesse d'avance			DaN (lbf)	2.000 (4.496)
Mandrino Spindle Broche Spindel	- Potenza motore AC - AC motor power - AC Motorantriebsleistung - Puissance du moteur AC		kW (Hp)	37 (50)	
	- Cono mandrino - Spindle taper - Spindelaufnahme - Cône de broche		ISO	50-DIN 69871	
	- Giri mandrino potenza costante - Spindle rotations with constant power - Spindeldrehzahlbereich bei konstanter Leistung - Tours de broche à puissance constante		g/min r.p.m. U.p.M. t.p.m.	235 - 4.000 (295 - 5.000) (345 - 6.000)	
	- Coppia massima mandrino - Max. spindle torque - Max. Spindeldrehmoment - Couple max. de la broche		Nm (lbf.ft)	1340 (1070)	

Tavole rototraslanti / Rotating-sliding tables / Dreh-Verschiebetische / Tables rotatives déplaçables					
		TRT7	TRT15	TRT30	TRT50
Dimensioni Dimensions Abmessungen Dimensions	mm (in)	1.000x1.000 (39,4x39,4)	1.500x1.500 (59x59)	2.000x2.500 (78,7x98,4)	2.500x2.500 (98,4x98,4)
		1.250x1.250 (49x49)	1.500x2.000 (59x78,7)	2.500x2.500 (98,4x98,4)	2.500x3.000 (98,4x118,1)
		1.500x1.750 (59x68,9)	2.000x2.000 (78,7x78,7)	2.500x3.000 (98,4x118,1)	3.000x3.000 (118,1x118,1)
					3.000x3.500 (118,1x137,8)
Portata Loading capacity Tischbelastung Capacité de poids	kg (lb)	7.000 (15.400)	15.000 (33.070)	30.000 (66.138)	50.000 (110.231)